



## **2XLUBE TURBO CF4/SG 15W40**

**Description** 

2XLUBE TURBO CF4/SG 15W40 is the highest quality diesel engine oils formulated with the highest quality base. It exceeds API CF-4 grade and meets European specification and most of other diesel engine maker's requirements. Its formulation of the best materials keeps the engine clean by reducing sludge and carbon build-up Also, it is excellent in terms of noise reducing, wear protection and high output.

**PERFORMANCE** 

Meets API CF-4/CF/SJ only performance requirements

Premium Motor Oil with Synthetic Base Oil and Special Additives Excellent Engine Cleanliness and Wear Protection and Power

Soft Engin Standing Prevents Engine Parts Damage Minimized Carbon Sludge Production during Combustion

Reduced Sediment Accumulation on Pistion Preventing Friction and Abrasion of Engine

Extended Engine Life, Noise Reduction and improved Power

## **Typical properties**

Items	Results	Test method
Appearance, conc	Yellowish Brown	VISUAL
	transparent	
Specific gravity, 15/4 ℃	0.870	ASTM D1298
Viscosity ( 40°C,mm²/s)	108.0	ASTM D445
Viscosity ( 100 °C,mm²/s)	14.9	ASTWID445
Viscosity index	143.0	ASTM D2270
Flash point, °C,COC	238.0	ASTM D92
Pour point, °C	-32.5	ASTM D92

<sup>\*</sup> Above test results are new fluid's typical properties, can be changed by quality improvement.

Application Heavy-duty truck/Bus with Diesel Engine

Light Truck /SUV with Diesel Engine
Passenger Car with Diesel Engine
All Vehicles with Diesel Engine

**Term of validity** 1 year in room from the date of manufacture at sealed state, 0 to 40 °C.

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.

