

TDS

VINA BUHMWOO

ISO 9001, MADE IN VIETNAM



ISO 9001:2008 Cert. No. :664066

VBC CI4/SL 15W40

Description

VBC CI4/SL 15W40 is the highest quality diesel engine oils formulated with the highest quality base oil Tri-Synthetic. It exceeds API CI-4 grade and meets European specification and most of other diesel engine maker's requirements. Its formulation of the best materials keeps the engine clean by reducing sludge and carbon build-up. Also, it is excellent in terms of noise reducing, wear protection and high output.

PERFORMANCE

Meets API CI-4/SL, ACEA E5/E7, MB228.3, 228.1, 229.1, Volvo VDS3,VDS2, MTU Type2,

Mack EOM-Plus, Cummins CES 20076/20077, MAN 3275 performance requirements

Excellent Engine Cleanliness, Wear Protection and Power Performance

Soft Engine Running Prevents Engine Parts Damage

Minimized Carbon Sludge Production during Combustion

Reduced Sediment Accumulation on Piston

Preventing Friction and Abrasion of Engine

Extended Engine Life, Noise Reduction and improved Power

Typical properties

Items	Results	Test method
Appearance, conc	Yellowish Brown transparent	VISUAL
Specific gravity, 15/4 °C	0.870	ASTM D1298
Viscosity (40 °C ,mm ² /s)	106.0	ASTM D445
Viscosity (100 °C ,mm ² /s)	15.0	
Viscosity index	146.0	ASTM D2270
Flash point, °C ,COC	232.0	ASTM D92
Pour point, °C	-35.0	ASTM D92

* Above test results are new fluid's typical properties, can be changed by quality improvement.

Application

Heavy-duty truck/Bus with Diesel Engine

Light Truck /SUV with Diesel Engine

Passenger Car with Diesel Engine

All Vehicles with Diesel Engine

Term of validity

1 year in room from the date of manufacture at sealed state, 0 to 40 °C.

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use thereof.