

Product Data Sheet

Castrol Vecton 15W-40 CI-4 Plus

Engine oil for heavy duty diesel engines

Description

Castrol Vector 15W-40 CI-4 Plus is a heavy duty diesel engine oil with exclusive System 5 Technology, which adapts to changing conditions to maximize performance in 5 key areas: Fuel Consumption, Oil Consumption, Oil Drain Interval, Component Life and Power

Application

Castrol Vecton 15W-40 CI-4 Plus is recommended for use in 4 stroke turbo-charged or naturally aspirated diesel engines where API CI-4 Plus, CI-4 or CH-4 performance is recommended. Please follow the manufacturers recommendations as described in the vehicles owners manual.

Advantages

- Fights oil thickening to help maintain better fuel economy-13 % less oil thickening*
- Fights piston deposits, resulting in lower oil consumption- 51% fewer deposits**
- Fights contaminants, resulting in longer drain intervals- 20% longer drain interval***
- Fights wear and corrosion, enhancing the life of critical engine components- 60% less wear****
- Fights soot to help maintain engine power- Up to 47% better that API CI-4 engine oils *****
- * Versus Seq IIIF (C-11984) limits
- ** Versus CAT 1R,Top Groove Fill
- *** Versus CI-4 engine oils, based on field trials
- ****Versus Cummins M-11 EGR limits, Crosshead weight loss
- ******Based upon Mack T-11 sooted oil viscosity increase results in an API CI-4 engine oil versus the API CI-4 Plus requirements

Typical Characteristics

| Name | Method | Units | Typical |
|----------------------------|------------|-----------|---------|
| Density @ 15°C | ASTM D4052 | g/ml | .878 |
| Viscosity, Kinematic 100°C | ASTM D445 | mm²/s | 15.71 |
| Viscosity, Kinematic 40°C | ASTM D445 | mm²/s | 120.4 |
| Viscosity Index | ASTM D2270 | None | 138 |
| Ash, Sulphated | ASTM D874 | % wt | 1.15 |
| Total Base Number, TBN | ASTM D2896 | mg KOH/g | 9.2 |
| Pour Point | ASTM D97 | °C | -39 |
| Pounds per Gallon | | lb/gallon | 7.31 |

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Product Performance Claims

API CI-4/CI-4 PLUS Cummins CES 20076, 20077

User Advice

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Vecton 15W-40 CI-4 Plus 16 Sep 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road , Wayne, NJ 07470

www.castrol.com